



BEASTX
BE ABSOLUTE STABLE



WWW.BEASTX.COM

MICROBEAST

3 AXIS MEMS GYRO SYSTEM FOR RC-MODEL AIRCRAFT

TECHNICAL DATA:

Operating voltage: 3,5V...8,5 V DC (Lipo 2S possible)
Prozessor: 32Bit ARM
Analog processing: 17Bit
Sensor technology: 3 MEMS angular rate sensors
Adjustable servo center pulse width:
Tail: 760µs / 960µs / 1520µs
Adjustable servo pulse rate:
Tail: 50 Hz / 165 Hz / 270 Hz / 330 Hz
Swashplate: 50 Hz / 65 Hz / 120 Hz / 200 Hz
Build in swashplate mixer:
Mechanical / 90° / 120° / 140°
Serial puls input: PPM / S-BUS / Spektrum*
Size: 34 x 25 x 13,5 mm
Weight without cable: approx. 20 g

CONTENT:

- MICROBEAST
- Receiver connection cables
- Mounting material
- Adjust tool
- Instruction manual

OPTIONAL ACCESSORIES:

- USB-Interface (settings / update)
- Spektrum-satellite adapter*

Info / Service / Downloads:

WWW.BEASTX.COM

MADE IN GERMANY

Hall 11.1/ NEC64
Spielwarenmesse
International Toy Fair
Nürnberg 04.02 - 09.02.2010

